




LED Highbay Light PESANTE

EXCELLENT DURABILITY With qualified LED chips installed in the high quality aluminum housing, the highbay is much more solid and durable. The lifespan of the high quality LED chip is up to 50,000 hours. The special designed upgrade heat sink fins on the back side could increase air contact area to speed up heat dissipation, which could also make contribution to extend the LED lifespan.

Driver Brand **Philips**




Lumileds Chips



PRODUCT ADVANTAGES AND FEATURES

- ◆ Hollow heat sink design increase more airflow for better heat dissipation
- ◆ High lumen LED , with 50,000hrs lifespan
- ◆ Imported optical lens , its luminous efficiency up to 95%
- ◆ High quality aluminum alloy , anti-corrosion , substantial , durable , artistic , practical . High craft manifesting production value of famous brand
- ◆ Designed diamond face reflection process , super high efficiency reflection light source , effectively enhance the brightness of the illumination

Dist (M)	Enadir (lx)
10m	52.29
20m	13.07
30m	5.810
40m	3.268
50m	2.092



Products parameter

Product Name :		UFO PESANTE		
Electric Data	Model Number :	R8384100	R8385150	R8386200
	Power :	100W	150W	200W
	Driver :	PHILIPS Dip Switch Power Adjustment with 1-10V dimming		
	Input :	AC85-265V , 50 /60 HZ		
	Power factor :	Pf>0.95		
	Driver Options :	On/Off /0-10V / Dali / Triac Dimmer		
	Power Efficiency :	92%		
	Light soure :	SMD		
Photometric Specifications	Lumen Efficiency (±5%)	130lm - 140lm/W		
	Colour Temperture :	3000k-4000k-6500k		
	Colour Rendering Index :	CRI>80		
	Beam angle :	90°		
Mechanical Specifications	Temperature range :	-20-55°C		
	Housing material :	Die-casting Aluminium		
	Optical material:	Polycarbonate Optics Lens		
	Lighning protection :	1.5-4KV		
	Protection class :	IP65		
	Body color :	Black		
	Life time :	>50000h		
Type Shapes :		Round		

AC85-265V 50-60Hz	Angle 90°	50000Hr Long Life	140Lm/W
----------------------	--------------	----------------------	---------

Projection direction	Pf>0.95	IK08	IP65
-------------------------	---------	------	------

3CCT	3000K Ra≥80	4000K Ra≥80	6500K Ra≥80
------	----------------	----------------	----------------

LED Chips

OSRAM	San'an	CREE	PHILIPS
-------	--------	------	---------

LED Drivers

ROCHLUX	LIFUD	PHILIPS	EAGLECRISE
---------	-------	---------	------------

