



LED BULKHEAD GAVINO

This is outdoor wall mounted bulkhead, made of die-cast aluminum body, PC cover, led chips. White/Black finished options with IP65 waterproof. CRI80/90 LED Chips and top quality isolated driver; it is very suitable for commercial projects. The standard version is with COB led chips, The input voltage 100-240VAC 50/60Hz as standard, but AC/DC 12V 24V can be customized as well. What is more, dimmable, motion sensor also can be available if needed.

PRODUCT ADVANTAGES AND FEATURES



- ◆ **Energy Efficiency:** LED bulkhead lights are a lot more energy-efficient than old-school incandescent or halogen bulbs. They use up to 80% less energy, but they put out the same amount of light.
- ◆ **Durability:** These lights are often moisture, impact, and corrosion-resistant and have IP ratings of IP65, making them perfect for outdoor use.
- ◆ **Variety of Types:** They come in a bunch of different versions. They have the regular ones. They also have emergency lights that have a battery backup. And they have sensor lights that turn on when you walk by them.



Products parameter

Product Name :		BULKHEAD LIGHT GAVINO		
Electric Data	Model Number :	R841912	R842018	R842128
	Power :	12W	18W	28W
	Driver :	Isolated driver included		
	Input :	100-240VAC / 220-240VAC 50/60Hz		
	Power factor :	Pf>0.95		
	Driver Options :	On/Off /0-10V / Dali / Triac Dimmer		
	Power Efficiency :	88%		
Photometric Specifications	Light source :	Epistar SMD Chips		
	Lumen Efficiency (±5%)	90lm - 100lm/W		
	Colour Temperture :	3000k-4000k-4500k-6000k-6500k		
	Colour Rendering Index :	CRI>80		
	Beam angle :	120°		
Mechanical Specifications	Working Temperature :	-25°C~+60°C		
	Working Temperature :	-30°C~+65°C		
	Housing material :	Die-casting Aluminium		
	Optical material:	PC Cover		
	Lighting protection :	1.5-4KV		
	Protection class :	IP65		
	Body color :	Black		
	Life time :	>50000h		
	Type Shapes :	Round, Oval		

5 Years Warranty

 100-240V 50-60Hz	 Angle 120°	 50000Hr Long Life	 150Lm/W
 Projection direction	 Pf>0.95	 IK07	 IP65
 3CCT	 3000K Ra≥80	 4000K Ra≥80	 6500K Ra≥80

LED Chips

			
---	---	---	---

LED Drivers

			
---	---	---	---

