


SMD DOWN LIGHT VICO

The Rochlux LED SMD Down light VICO adopts high lumen SMD LED, PC diffuser with even light output. White, silver, chrome surface treatment available for different applications. Triac dimmable and Zigbee dimmable version shares great popularity by the excellent dimming effect. These lights suitable for, commercial and residential applications office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.



PRODUCT ADVANTAGES AND FEATURES




- ◆ **UNIQUE HEAT SINK DESIGN** : Artistic heat dissipation structure design with excellent heat dissipation effect. Guaranteed long-term maintenance.
- ◆ **SMD CHIPS** : Adopt high luminous efficiency 5630/2835 SMD LED, low degradation. Up to 85 Lm/W, high brightness. Environment friendly.
- ◆ **High CRI** : restore true beauty. Ideal choice for retail application, enjoy the fun of the light.
- ◆ **Intelligent Control** : It can be dimming with SmartHome Control System. WiFi & Remote & Touch dimming. Make the light bright and the color change can be intelligent and more easier.
- ◆ **Discover Total Lighting Control** : 3CCT LED Downlights, offering a dynamic spectrum of lighting options. With 3 color temperatures -you have the power to create the perfect ambience.



Products parameter

Product Name :		LED DOWN LIGHT VICO		
Electric Data	Model Number :	R844710	R844717	R844924
	Power :	10W	17W	24W
	Driver :	ROCHLUX		
	Input :	AC200-240V , 50 /60 HZ		
	Power factor :	Pf>0.9		
	Driver Options :	On/Off / Triac Dimmer/ Zigbee		
	Power Efficiency :	92%		
Photometric Specifications	Light source :	SMD2835 LED		
	Lumen Efficiency (±5%)	95lm/W		
	Colour Temperture :	3000k-4000k-6000k		
	Colour Rendering Index :	CRI>80		
Mechanical Specifications	Beam angle :	110°		
	Temperature range :	20-50°C		
	Housing material :	UL 94 V0 fire rated PC+Aluminum		
	Optical material:	PC diffuser		
	Lighning protection :	1.5-4KV		
	Protection class :	IP44		
	Body color :	White,		
	Life time :	30000h		
	Type Shapes :	Round		

Model No.	Power	Luminous Flux	Beam Angle	Input Voltage	Product Size	Cutout Size
R844710	10	950lm	110°	AC200-240V	Ø113-59mm	Ø90-105mm
R844717	17	1615lm	110°	AC200-240V	Ø174-69mm	Ø150-160mm
R844928	24	2280lm	110°	AC200-240V	Ø244-85mm	Ø200-215mm



LED Chips



LED Drivers

