



SURFACE MOUNTED LANZO



This is our slim flush mounted ceiling light, the thickness is only 60mm. The bottom is metal materials, and cover is PC, high lumens output. The light sources are SMD LED Chips with lens. It is widely used for residential places such as living room, kitchen room, bedroom etc, or commercial lighting for offices, shopping mall.



PRODUCT ADVANTAGES AND FEATURES

- ◆ Energy Efficiency: These LEDs consume significantly less energy than conventional bulbs, reducing electricity costs and environmental impact.
- ◆ Longevity: LED downlights boast a longer lifespan, minimizing the need for frequent replacements and maintenance.
- ◆ Design Flexibility: Available in various sizes and colors, surface mount LEDs can be seamlessly integrated into any design aesthetic.
- ◆ Easy Installation: Unlike recessed lighting, surface mount LEDs do not require extensive ceiling voids, making them easier and quicker to install.

5 Years Warranty

Products parameter

Product Name :		SURFACE MOUNTED LIGHT LANZO		
Electric Data	Model Number :	R842818	R842921	R843040
	Power :	18W	21W	40W
	Driver :	ROCHLUX		
	Input :	100-240VAC / 220-240VAC 50/60Hz		
	Power factor :	Pf>0.95		
	Driver Options :	Included Top quality driver.free flicker		
Photometric Specifications	Power Efficiency :	85%		
	Light source :	Epistar/Bridglux/OSRAM		
	Lumens :	90Lm - 100Lm/W		
	Colour Temperture :	3000k-4000k-6500k		
	Colour Rendering Index :	CRI>80		
Mechanical Specifications	Beam angle :	120°		
	Working Temperature :	-35°C~+55°C		
	Housing material :	SPCC+PMMA Cover, whole white finished		
	Optical material:	PMMA Defuser		
	Lighning protection :	1.5-4KV		
	Protection class :	IP40		
	Body color :	White		
	Life time :	>50000h		
	Type Shapes :	Round		

 100-240v 50-60Hz	 Pf>0.95	 SMD LED	 50000H Long Life
 projection direction	 IK02	 Angle 120°	 IP40


 3CCT	 3000K Ra>80	 4000K Ra>80	 6500K Ra>80
---	---	---	---

LED Chips

			
---	---	---	---

LED Drivers

			
---	---	---	---

		
Product Watts	D	H
18W	Ø280	65mm
21W	Ø350	65mm
40W	Ø350	65mm