

LED STEP LIGHT RIZO



The RIZO Wall Recessed Light is a durable architectural lighting solution designed for safe and elegant illumination of indoor and outdoor spaces. Its high-quality die-cast aluminum housing provides excellent strength, heat dissipation, and long-term reliability. The recessed design creates a clean and minimal appearance while providing comfortable downward illumination with reduced glare. High-efficiency LED light sources ensure dependable performance with low energy consumption and consistent light output. The IP65 protection rating makes the luminaire resistant to dust and water, allowing reliable use in demanding environments.




PRODUCT ADVANTAGES AND FEATURES

- ◆ Durable Die-Cast Aluminum Housing for excellent strength, heat dissipation, and long service life.
- ◆ IP65 Weather Protection suitable for both indoor and outdoor wall installation.
- ◆ Energy-Efficient LED Technology provides reliable illumination with reduced power consumption.
- ◆ Low-Glare Recessed Design delivers comfortable and controlled downward lighting.
- ◆ Protective Frosted/Tempered Glass ensures smooth light distribution and enhanced durability.
- ◆ Multiple Sizes & Wattages available in 3W, 6W, and 15W for different architectural applications.

Products parameter

Electric Data	Product Name :	STEP LIGHT RIZO
	Model Number :	R853006
	Power :	6W
	Driver :	ROCHLUX
	Input :	220V-240V AC 50~60Hz
Photometric Specifications	Power factor :	PF >0.95
	Light source :	LED / Lumileds 2835
	Luminous Flux :	161lm
	Lumen Efficiency :	27lm/W
	Colour Temperature :	3000K-4000K-6000K
	Colour Rendering Index :	CRI >80
	Beam angle :	46.28°
Mechanical Specifications	Housing material :	Die-casting Aluminium
	Optical material :	Frost Tempered Glass
	Protection class :	IP65
	IK class :	IK08
	Body color :	Dark grey / black appearance
	Life span :	>50000H
	Type Shapes :	Square / Wall Recessed
	Size :	6W : 110 x 110 x 98



5 Years Warranty

Shows Colors True & Natural
High CRI

AC220-240V 50-60Hz	IK08	161Lm	50000Hr Long Life
Angle 46.28°	COB LED	Pf>0.95	IP65
3CCT	3000K Ra>80	4000K Ra>80	6000K Ra>80

LED Chips

OSRAM	Sanan	CREE	bridgelux
-------	-------	------	-----------

LED Drivers


ROCHLUX	LIFUD	PHILIPS	EAGLE RISE
---------	-------	---------	------------




Technical Parameter

Model No	Power	Item Code	Beam Angle	Input Voltage	Lamp Size (mm)	Color Temperature	Luminous Flux	Angle
R852903	3W	R3652D-3W	36°	220v-240vAC 50/60HZ	246x246x87	3K-4K-6K	81Lm	ONE WAY
R853006	6W	R3654D-6W	46.28°	220v-240vAC 50/60HZ	110x110x98	3K-4K-6K	160.9Lm	
R853115	15W	R3654D-15W	36x154°	220v-240vAC 50/60HZ	232x78.5x116	3K-4K-6K	394Lm	


Product Dimensions :



R852903



R853006



R853115

